

# NTM-716

## 6" Air-Tight Aluminum Shallow Baffle Cone Reflector

|             |  |
|-------------|--|
| Type        |  |
| Project     |  |
| Catalog No. |  |
| Notes       |  |

### CONSTRUCTION

Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare.

### MOUNTING

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Socket can be mounted directly to trim without bracket.

### COMPATIBLE LAMP / HOUSINGS


- 50W R20/PAR20 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)
- 60W A19 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)
- 75W BR30/PAR30 Maximum (NHIC-27QAT, NHRIC-27QAT, NH-27Q, NHR-27Q, NFBIC-6INCATA)
- 90W R40/PAR38 Maximum (NFBIC-6INCATA)

### LISTINGS

- cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



## 6" Air-Tight Aluminum Shallow Baffle Cone Reflector

Catalog No. \_\_\_\_\_  
**NTM-716WAL** = 6" White Air-Tight Aluminum Shallow Baffle Cone Reflector, White Flange

## Compatible Housings

Catalog No. \_\_\_\_\_  
**NHIC-27QAT** = ICAT Shallow New Construction / 75W max.  
**NHRIC-27QAT** = ICAT Shallow Remodel / 75W max.  
**NH-27QAT** = Non-IC Shallow New Construction / 75W max.  
**NHR-27QAT** = Non-IC Shallow Remodel / 75W max.  
**NFBIC-6INCATA** = ICAT Fire Rated New Construction / 90W Max

Example: **NTM-716WAL** = 6" White Air-Tight Aluminum Shallow Baffle Cone Reflector, White Flange